



# PURE Chalk

## product data sheet

### **This Product**

This paint is ideal for furniture and walls creating a matt chalk finish that you can even write on (with chalk) Pure Chalk is easy to use, low odour and water clean-up.

### **Our Environment**

Contains 34 grams per litre VOC. (APAS target 100 grams per litre\*). This product is manufactured to Murobond's environmental standard.

### **Your Environment**

Low odour, water clean-up, fast dry.

### **Preparation**

Remove all loose and flaking material, ensure surface is clean and free of dirt, mould, dust or other foreign material. Fill surface imperfections with appropriate fillers and sand off excess. Unsound old, oil-based painted, and new / bare surfaces should be primed – this includes filled areas. Pure Chalk may be applied directly to clean, sound surfaces previously painted with water based paint.

### **Priming**

Unsound, oil-based painted, plasterboard, timber (not tannin rich), fillers, aluminium, galvanised iron, fibre cement, cement render, brick, block should be primed with one coat of Pure Chalk Primer.

Tannin rich timbers may require an oil or spirit base stain block to prevent leaching.  
Hard-set (white set) will need Murobond Mineral Silicate Primer first.

### **Application**

Stir then apply two coats of Pure Chalk Paint by brush, roller (mid to short nap) or spray allowing 4 hours between coats (longer in colder conditions). If you are going to write on it, allow 2 days to fully dry beforehand.

### **Coverage**

11m<sup>2</sup> per litre approximately.

### **Clean-up**

Water. Thinning is not recommended.

### **Maintenance**

Use a damp cloth to remove chalk.

### **Storage**

Store in cool dry location.

### **Precautions**

Do not apply if surface or air temperature is below 10°C or above 30°C. Protective clothing such as glasses and gloves are advised during use. Do not swallow.

Issue date: September 2013

# MUROBOND