Safety Data Sheet

WOODWASH EXTERIOR

NON-HAZARDOUS ACCORDING TO THE CRITERIA OF WORKSAFE AUSTRALIA

If poisoning occurs contact a doctor or The Poison Information Centre 131126

1. PRODUCT & SUPPLIER IDENTIFICATION

Trade Name Woodwash Exterior

Product Class Alkyd emulsion.

Intended Use Wood Coating.

Supplier Murobond Coatings Pty Ltd 73 Dickson Avenue

ARTARMON NSW 2064

 Telephone Number
 02 9906 7299

 Facsimile Number
 02 9439 7593

2. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS	CAS NO	CONTENT	MAXIMUM EXPOSURE LIMITS
ALKYD EMULSION	Proprietary	< 30%	None Assigned
WATER)	7732-18-5	30 – 60%	None Assigned

3. HAZARDS IDENTIFICATION

Emergency Overview

Appearance White or coloured liquid, mild odour.

Route(s) of Entry Eye contact, ingestion, inhalation and skin contact.

Closed containers may rupture when exposed to extreme heat.

Acute Exposure

Eyes Direct contact with this material causes severe eye irritation.

Symptoms may include stinging, tearing, redness and swelling.

Ingestion Toxic if swallowed. Ingestion (swallowing) may irritate the mouth,

throat and stomach. Ingestion is not an anticipated route of expo-

sure for this material in industrial use.

Inhalation Inhalation of vapour or aerosol causes irritation of the respiratory

tract (nose, throat and lungs).

Skin Contact causes skin irritation. Prolonged or repeated skin contact

can result in defatting and drying the skin

Carcinogenicity This product does not contain 0.1% or more of any substance

which is listed as a carcinogen by Worksafe

4. FIRST AID MEASURES

Eyes If in eyes, hold eyelids apart and flush the eye continuously with

running water. Continue flushing until advised to stop by the

Poisons Information Centre or a doctor, or for at least 15 minutes.

Ingestion Rinse mouth with water. Give water to drink. Do NOT induce

vomiting. Seek medical attention immediately.

Inhalation First aid is not generally required. Remove to fresh air. If in doubt

contact the Poisons Information Centre (Ph. 131126) or a doctor.

Skin If skin or hair contact occurs, remove contaminated clothing and

flush skin and hair with running water. Wash clothing before re-use.

5. FIRE FIGHTING MEASURES

Flash Point >93°C

General Hazards Containers of this material may build up pressure if exposed

to heat.

Fire Fighting

Extinguishing Media Use carbon dioxide, foam, dry chemical or water fog to extinguish

fire.

Fire Fighting Equipement Wear self-contained breathing apparatus (SCBA) and full fire

fighting protective clothing. Thoroughly decontaminate all

protective equipment after use.

Fire & Explosion Hazards This material will not burn unless it is evaporated to dry.

Hazardous Combustion

Products Combustion may produce carbon monoxide, carbon dioxide and

irritating or toxic vapours and gases.

6. ACCIDENTAL RELEASE

Small Spills Absorb the liquid with inert material such as dry sand or earth

and place it in a chemical waste container.

Large Spills Persons not wearing protective equipment should be evacuated

from the area of spill until cleanup has been completed. Stop leak at source when it is safe to do so. Dike and pump the liquid

into waste containers.

7. HANDLING & STORAGE

Store in a cool dry area, away from direct sunlight. Keep containers closed

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines No limit value established for this product

Engineering Controls Use in a well ventilated area

Personal Protection Protective clothing such as gloves, overalls, and glasses should

be worn.

9. PHYSICAL & CHEMICAL PROPERTIES

Appearance & Odour: White milky liquid with mild acrylic odour.

Boiling Point: Not applicable
Flash Point: Not applicable
Vapour Density: Not available

Specific Gravity: 1.40

Evaporation Rate: Not available Flammability Limits: Not applicable

Solubility in Water: Miscible pH: 8 – 10

Volatile Organic

Compound: 52g/litre

10. STABILITY & REACTIVITY

Stability Stable

Hazardous

Polymerisation Will not occur.

Incompatibility Avoid contact with strong oxidising agents

Conditions To Avoid Warm storage.

Hazardous

Decomposition Products Incomplete combustion can yield carbon monoxide &

toxic vapours.

Hazardous Reactions None known.

11. TOXICOLOGICAL INFORMATION

Effects of prolonged exposure

Eyes May irritate eyes.

Skin Contact with skin may result in mild irritation.

Inhalation With poor ventilation, may cause irritation to mucous

membranes and headaches.

Ingestion No effects anticipated. Large quantities may cause nausea/vomiting.

Chronic Effects None expected.

12. ECOLOGICAL INFORMATION

Free of Hazardous Air Pollutants (HAPS). Avoid contaminating Waterways.

13. DISPOSAL INFORMATION

Refer to State/Territory Land Waste Management Authority.

Do not pour down drains. Normally suitable for incineration by approved agent.

14. TRANSPORT INFORMATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code), IMDG & IATA.

15. REGULATORY INFORMATION

Non Hazardous according to the criteria of Worksafe Australia.

Hazard Category None Poisons Schedule None

16. OTHER INFORMATION

All components within this product are listed on the AICS.

Reason Issued: Revised SDS Prepared By: Murobond Coatings Pty Ltd Date: July 2019

This information is provided in good faith and is correct to the best of Murobond's knowledge at the date of issue. Murobond makes no representation as to its completeness or accuracy. Customers should determine the suitability or otherwise of this product for their intended purpose before using. Murobond disclaims responsibility for damage of any kind resulting from the use of this information.

THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESSED OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES.