



PURE Chalk

product data sheet

This Product

This paint is ideal for furniture and walls creating a matt chalk finish that you can even write on (with chalk) Pure Chalk is easy to use, low odour and water clean-up.

Our Environment

Contains 34 grams per litre VOC. (APAS target 100 grams per litre*). This product is manufactured to Murobond's environmental standard.

Your Environment

Low odour, water clean-up, fast dry.

Preparation

Remove all loose and flaking material, ensure surface is clean and free of dirt, mould, dust or other foreign material. Fill surface imperfections with appropriate fillers and sand off excess. Unsound old, oil-based painted, and new / bare surfaces should be primed – this includes filled areas. Pure Chalk may be applied directly to clean, sound surfaces previously painted with water based paint.

Priming

Unsound, oil-based painted, plasterboard, timber (not tannin rich), fillers, aluminium, galvanised iron, fibre cement, cement render, brick, block should be primed with one coat of Pure Chalk Primer.

Tannin rich timbers may require an oil or spirit base stain block to prevent leaching.
Hard-set (white set) will need Murobond Mineral Silicate Primer first.

Application

Stir then apply two coats of Pure Chalk Paint by brush, roller (mid to short nap) or spray allowing 4 hours between coats (longer in colder conditions). If you are going to write on it, allow 2 days to fully dry beforehand.

Coverage

11m² per litre approximately.

Clean-up

Water. Thinning is not recommended.

Maintenance

Use a damp cloth to remove chalk.

Storage

Store in cool dry location.

Precautions

Do not apply if surface or air temperature is below 10°C or above 30°C. Protective clothing such as glasses and gloves are advised during use. Do not swallow.

Issue date: September 2013

MUROBOND