

Safety Data Sheet

WOODWASH EXTERIOR

NON-HAZARDOUS ACCORDING TO THE CRITERIA OF WORKSAFE AUSTRALIA

If poisoning occurs contact a doctor or The Poison Information Centre 131126

1. PRODUCT & SUPPLIER IDENTIFICATION

<i>Trade Name</i>	Woodwash Exterior
<i>Product Class</i>	Alkyd emulsion.
<i>Intended Use</i>	Wood Coating.
<i>Supplier</i>	Murobond Coatings Pty Ltd 73 Dickson Avenue ARTARMON NSW 2064
<i>Telephone Number</i>	02 9906 7299
<i>Facsimile Number</i>	02 9439 7593

2. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS	CAS NO	CONTENT	MAXIMUM EXPOSURE LIMITS
ALKYD EMULSION	Proprietary	< 30%	None Assigned
WATER)	7732-18-5	30 – 60%	None Assigned

3. HAZARDS IDENTIFICATION

Emergency Overview

<i>Appearance</i>	White or coloured liquid, mild odour.
<i>Route(s) of Entry</i>	Eye contact, ingestion, inhalation and skin contact.

Closed containers may rupture when exposed to extreme heat.

Acute Exposure

<i>Eyes</i>	Direct contact with this material causes severe eye irritation. Symptoms may include stinging, tearing, redness and swelling.
<i>Ingestion</i>	Toxic if swallowed. Ingestion (swallowing) may irritate the mouth, throat and stomach. Ingestion is not an anticipated route of exposure for this material in industrial use.
<i>Inhalation</i>	Inhalation of vapour or aerosol causes irritation of the respiratory tract (nose, throat and lungs).
<i>Skin</i>	Contact causes skin irritation. Prolonged or repeated skin contact can result in defatting and drying the skin
<i>Carcinogenicity</i>	This product does not contain 0.1% or more of any substance which is listed as a carcinogen by Worksafe

4. FIRST AID MEASURES

<i>Eyes</i>	If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
<i>Ingestion</i>	Rinse mouth with water. Give water to drink. Do NOT induce vomiting. Seek medical attention immediately.
<i>Inhalation</i>	First aid is not generally required. Remove to fresh air. If in doubt contact the Poisons Information Centre (Ph. 131126) or a doctor.
<i>Skin</i>	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Wash clothing before re-use.

5. FIRE FIGHTING MEASURES

<i>Flash Point</i>	>93°C
<i>General Hazards</i>	Containers of this material may build up pressure if exposed to heat.
<i>Fire Fighting</i>	
<i>Extinguishing Media</i>	Use carbon dioxide, foam, dry chemical or water fog to extinguish fire.
<i>Fire Fighting Equipment</i>	Wear self-contained breathing apparatus (SCBA) and full fire fighting protective clothing. Thoroughly decontaminate all protective equipment after use.
<i>Fire & Explosion Hazards</i>	This material will not burn unless it is evaporated to dry.
<i>Hazardous Combustion Products</i>	Combustion may produce carbon monoxide, carbon dioxide and irritating or toxic vapours and gases.

6. ACCIDENTAL RELEASE

<i>Small Spills</i>	Absorb the liquid with inert material such as dry sand or earth and place it in a chemical waste container.
<i>Large Spills</i>	Persons not wearing protective equipment should be evacuated from the area of spill until cleanup has been completed. Stop leak at source when it is safe to do so. Dike and pump the liquid into waste containers.

7. HANDLING & STORAGE

Store in a cool dry area, away from direct sunlight. Keep containers closed

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<i>Exposure Guidelines</i>	No limit value established for this product
<i>Engineering Controls</i>	Use in a well ventilated area
<i>Personal Protection</i>	Protective clothing such as gloves, overalls, and glasses should be worn.

9. PHYSICAL & CHEMICAL PROPERTIES

<i>Appearance & Odour:</i>	White milky liquid with mild acrylic odour.
<i>Boiling Point:</i>	Not applicable
<i>Flash Point:</i>	Not applicable
<i>Vapour Density:</i>	Not available
<i>Specific Gravity:</i>	1.40
<i>Evaporation Rate:</i>	Not available
<i>Flammability Limits:</i>	Not applicable
<i>Solubility in Water:</i>	Miscible
<i>pH:</i>	8 – 10
<i>Volatile Organic Compound:</i>	52g/litre

10. STABILITY & REACTIVITY

<i>Stability</i>	Stable
<i>Hazardous Polymerisation</i>	Will not occur.
<i>Incompatibility</i>	Avoid contact with strong oxidising agents
<i>Conditions To Avoid</i>	Warm storage.
<i>Hazardous Decomposition Products</i>	Incomplete combustion can yield carbon monoxide & toxic vapours.
<i>Hazardous Reactions</i>	None known.

11. TOXICOLOGICAL INFORMATION

Effects of prolonged exposure

<i>Eyes</i>	May irritate eyes.
<i>Skin</i>	Contact with skin may result in mild irritation.
<i>Inhalation</i>	With poor ventilation, may cause irritation to mucous membranes and headaches.
<i>Ingestion</i>	No effects anticipated. Large quantities may cause nausea/vomiting.
<i>Chronic Effects</i>	None expected.

12. ECOLOGICAL INFORMATION

Free of Hazardous Air Pollutants (HAPS). Avoid contaminating Waterways.

13. DISPOSAL INFORMATION

Refer to State/Territory Land Waste Management Authority.

Do not pour down drains. Normally suitable for incineration by approved agent.

14. TRANSPORT INFORMATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code), IMDG & IATA.

15. REGULATORY INFORMATION

Non Hazardous according to the criteria of Worksafe Australia.

Hazard Category None

Poisons Schedule None

16. OTHER INFORMATION

All components within this product are listed on the AICS.

Reason Issued: Revised SDS Prepared By: Murobond Coatings Pty Ltd Date: July 2024

This information is provided in good faith and is correct to the best of Murobond's knowledge at the date of issue.

Murobond makes no representation as to its completeness or accuracy. Customers should determine the suitability or otherwise of this product for their intended purpose before using. Murobond disclaims responsibility for damage of any kind resulting from the use of this information.

THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESSED OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES.

MUROBOND